Book Chapter

Sustainable Cooking Based on a 3 kW Air-Forced Multifuel Gasification Stove Using Alternative Fuels Obtained from Agricultural Wastes

Elías Hurtado Pérez¹, Oscar Mulumba Ilunga^{2,3}, David Alfonso Solar¹, María Cristina Moros Gómez¹ and Paula Bastida-Molina^{1*}

¹Instituto Universitario de Investigación en Ingeniería Energética, Universitat Politècnica de Valencia UPV, Spain

²Mechanical Department, Higher Institution of Applied Techniques ISTA, Congo

³Centre for Studies and Research on Renewable Energy Kitsisa Khonde CERERK, Congo

***Corresponding Author:** Paula Bastida-Molina, Instituto Universitario de Investigación en Ingeniería Energética, Universitat Politècnica de Valencia UPV, 46022 Valencia, Spain

Published **February 15, 2021**

This Book Chapter is a republication of an article published by Paula Bastida-Molina, et al. at Sustainability in September 2020. (Hurtado Pérez, E.; Mulumba Ilunga, O.; Alfonso Solar, D.; Moros Gómez, M.C.; Bastida-Molina, P. Sustainable Cooking Based on a 3 kW Air-Forced Multifuel Gasification Stove Using Alternative Fuels Obtained from Agricultural Wastes. Sustainability 2020, 12, 7723. <https://doi.org/10.3390/su12187723>)

How to cite this book chapter: Elías Hurtado Pérez, Oscar Mulumba Ilunga, David Alfonso Solar, María Cristina Moros Gómez, Paula Bastida-Molina. Sustainable Cooking Based on a 3 kW Air-Forced Multifuel Gasification Stove Using Alternative Fuels Obtained from Agricultural Wastes. In: Maria Helena

Henriques, editor. Prime Archives in Sustainability. Hyderabad, India: Vide Leaf. 2021.

© The Author(s) 2021. This article is distributed under the terms of the Creative Commons Attribution 4.0 International License(<http://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Author contributions: Conceptualization: OMI and EHP. Methodology, OMI. Software, EHP. Validation: OMI, EHP and DA. Formal analysis: DA, MCMG and PBM. Investigation: OMI and EHP. Resources: OMI and EHP. Data: DA, OMI and MCMG. Writing (original draft preparation): OMI. Writing (review and editing): EHP and MCMG. Visualization: PBM, DA. Supervision: PBM, DA and MCMG. Project administration: MCMG, PBM and EHP. Results interpretation: all authors. All authors have read and approved the final manuscript.

Conflicts of Interest: The authors declare no conflict of interest.

Abstract

In this research work, a 3 kW stove based on biomass gasification, together with a fuel obtained from agriculture wastes as an alternative to the commonly used charcoal, have been developed looking for a sustainable cooking in poor communities. Alternative fuel (BSW) are briquettes obtained by carbonization and densification of agricultural solid wastes. Two laboratory methods, water boil test (WBT) and controlled kitchen test (CCT) were used to analyze the performance of this approach by comparing the proposed improved stove (ICS-G) with the traditional one (TCS), when using both types of fuels: charcoal and BSW. Results indicate that consumption of charcoal decreases by 61% using the improved ICS-G stove instead of the traditional TCS. Similar fuel savings are obtained when using BSW fuels. BSW fuel allows for a carbon monoxide (CO) emission reduction of 41% and 67%, and fine particles (PM) in a 84% and 93%, during the high and low power phases of the tests, respectively. Use of BSW fuel and ICS-G stove

instead of the TCS stove with charcoal, provides a cooking time reduction in a 18%, savings of \$353.5 per year and family in the purchase of fuel and an emission reduction of 3.2 t CO₂/year.family.

Keywords

Cook Stove; Alternative Fuel; Gasification; Sustainability

Abbreviations

BC- Black Carbon; BSW- Solid Fuel Briquettes; CCT- Cooking Controlled Test; ER-CO₂- Carbon dioxide Emission Reduction; FCR- Fuel Consumption Rate; HP- High Power WBT Phase; ICS-G- Improved Gasification Stove; LP- Low Power WBT Phase; PM- Particle Matter; PEMS- Portable Emissions Measurement System; DRC- Democratic Republic of Congo; SA- Stequiometric Air; SFC- Specific Fuel Consumption; SEC- Specific Energy Consumption; SGR- Specific Gasification Rate; TCS- Traditional Stove; WBT-Water Boiling Test

Introduction

In recent decades, the demand for primary energy resources has considerably increased due to the high growths, both in world population and demand, while renewable resources, such as firewood, are often poorly managed in this scenario of increasing demand. Consequently, the proper use of these resources becomes mandatory for a sustainable development [1]. Currently, in the world about three billion people depend on solid fuels, such as firewood and charcoal, for cooking food and heating, without having access to clean cooking methods [2-5]. Solid fuels are the main source of energy used for heating and cooking in many urban and suburban communities in sub-Saharan African countries, representing more than 80% of the primary energy supply of these areas [6-8]. The traditional cooking system most used in these communities is based on burning coal or firewood on stoves with the pots placed on top, resulting in a process of very low thermal efficiency and, therefore, in an excessive fuel consumption with the consequent

environmental damage [9-11], including excessive CO₂ emissions, thus contributing to global warming and climate change [12]. Significant efforts are in progress to improve cooking stoves and limit the above-mentioned drawbacks. It has been found that fan-assisted cookstoves produced both lower concentrations of flue gases and particulate matter [13]. Positive experience in Rwanda promoting biomass pellets and a fan micro-gasification improved cookstove as a clean cooking alternative to charcoal has been obtained [14]. Gasifier Cookstove using biochar improves energy efficiency and air quality [15] and investigation on the gas production from a gasifier cookstove indicates the importance of primary air to reduce tars and increases combustion [16]. This paper addresses all these aspects: gasifier implementation, energy efficiency, air quality, pellets use, etc., looking for the improvement of cook stove both in the technical and economical aspects with special emphasis in the use of agriculture wastes to reduce the environmental impact of cooking in under-developed countries.

Although agriculture and timber industry are considered as the main responsible for large-scale deforestation, energy supply for food cooking [17] has also an important contribution to deforestation and land degradation. The collection of firewood and the production of charcoal for cooking can have a significant impact on local ecosystems, particularly in overpopulated areas [18, 19]. Due to the fight against the climate change and the search for energy security, biomass resources are becoming more important than ever, given they can be considered as renewable and sustainable source of energy, neutral for climate impact [20] and socially viable. This is possible if: (i) they are collected in sustainably managed forests, where each cut tree is replanted directly; and, (ii) the wood is burned using appropriate technologies to maximize energy efficiency and minimize harmful emissions inside the house (CO and PM) and to the atmosphere (CO₂) [21]. In sub-Sahara African countries, burning agricultural wastes (including stems, herbs and leaves) is the easiest and most economical way to eliminate the volume of those wastes. Outdoors incineration allows for a fast elimination of previous crops wastes, as well as the pruning and cleaning of the crop area. It is estimated that burning biomass, such as wood,

leaves, trees and pastures, including agricultural wastes, is responsible for a 40% of carbon dioxide (CO₂), 32% of carbon monoxide (CO), 20% of suspended fine particles (PM) and 8% of others emissions to the atmosphere [22, 23] of these areas. These biomass wastes could be instead used in cooking stoves, using a biomass gasification technology, and thus be an important part of solving these emissions problems [24, 25]. The amount of peanut shell waste produced annually in the Democratic Republic of the Congo is estimated at 114,000 tons and that of rice husk is around 133,200 t / year [26, 27]. The province of Bandundu, to which the present study is applied, being a province totally dedicated to agriculture, represents almost 20% of the production of agricultural residues in the DRC. Using improved gasification stoves, energy efficiencies can easily reach values greater than 60%, compared to 30-40% of the current ones [28, 29]. Most of the technologies currently in use consist of enhanced direct combustion ICS with a ceramic combustion chamber. This approach simply involves directing much of the combustion energy to the pot. In this system, it is difficult to improve the quality of combustion because the air supply is naturally ventilated and therefore difficult to regulate, which leads to incomplete combustion with a direct negative consequence on energy efficiency and polluting emissions. In order to reduce the consumption of firewood and CO₂ emissions in cooking activities, a 3 kW power stove has been optimized using the biomass micro-gasification principle. Additionally, to reduce the consumption of forest biomass, an alternative fuel to charcoal consisting of briquettes produced by carbonization and densification of agricultural solid wastes (peanut husk and rice husk, mainly) has been developed. To verify these improvement approaches, two laboratory test methods: the boiling water test (WBT) and the controlled cooking test (CCT), have been applied to the traditional stove (TCS) and the new one we are proposing (ICS-G) , using in both cases charcoal and BSW briquettes as fuels.

Materials and Methods

Study Case

The study was conducted in the city of Bandundu located 409 km from the DRC capital Kinshasa and in an essentially agricultural region. The population size is estimated at 3,673,000 inhabitants and 90% of the population is considered dependent on biomass-firewood for cooking food. The average family size is six people and the eating habits are such that only one large meal is served daily.

Fuels

The fuel currently used for food cooking in sub-Saharan Africa countries is charcoal. We have deduced its main characteristics by application of standards biomass characterization techniques [30]. Obtained results are detailed in table 1.

There are many different solid biomass residues from agricultural activities in the Democratic Republic of the Congo (DRC). In this work, we have selected as sources for fuel for cooking activities those with the better thermo-physical properties. The proposed fuel (BSW) for cooking are briquettes with a cylindrical shape of 2 cm in diameter and 3.5 cm in length (figure 1), so they are well adjusted to the typical cooking stoves. The briquettes are made from solid agricultural wastes, such as peanut shells and rice husks. Manufacturing of briquettes follows the following steps:

1st) Carbonization: carried out in a traditional furnace composed of a cylindrical metal barrel 80cm in diameter and 120cm high. The metal barrel has about thirty vent holes. 3cm at its lower base. The removable upper base has a 10cm diameter and 100cm high chimney. Char waste is introduced from the top with a quantity of 20 kg of solid waste (rice husks or peanuts). The fire is lit from the top of this furnace. The carbonization system is endothermic in oxygen, evolving at temperatures between 250-500°C for 2 to 3 hours. After this, holes in the lower base are covered and the lid is closed until cooled, which can last 3 to 4 hours. The carbonization yield varies between 18-20%.

2nd) Grinding: the char waste is placed in a mortar with an artisanal pestle to convert the charred waste into a fine powder with a grain size of 1 mm.

3rd) Binding: the resulting powder, combined with a binder biomass (paper pulp and cassava fibers), is mixed properly up to have a good homogenization.

4th) Densification: this mixture is manually densified to form the briquettes; and

5th) Drying: the briquettes are dried in the sun for three days before their use.

Three types of briquettes were manufactured with the dosages detailed in Table 2. Their elemental composition and the different thermo-physical properties of these briquettes, respectively, are shown at tables 3 and 4. These values were obtained following current regulations for this type of characterization [30]. From the cooking tests carried out summarized in table 4, it results that BSW3 structure is the most adequate to be used, given its higher calorific value.

Table 1: Thermo-physical characteristics of traditional charcoal.

Bulk density [kg.m ⁻³]	Moisture content	Volatile matter	Ash content	Fixed Carbon	HHV [MJ.kg ⁻¹]	LHV [MJ.kg ⁻¹]
365	7%	13%	2%	85%	30,2	29,8

Table 2: Composition of the different types of briquettes [% mass].

Type	E1	E2	E3	E4	E5
BSW 1	50%	-	20%	15%	15%
BSW 2	-	50%	30%	10%	10%
BSW 3	-	20%	50%	15%	15%

(E1 = biochar rice, E2 = biochar peanut, E3 = sawdust, E4 = paper paste, E5 = cassava xilema fiber)

Table 3: BSW elemental composition

Type	C	H	N	O	S
BSW 1	51,70%	2,40%	0,70%	45,20%	0,00%
BSW 2	52,50%	3,20%	0,70%	43,60%	0,00%
BSW 3	50,70%	2,70%	0,60%	46,00%	0,00%

Table 4: BSW thermo-physical characteristics.

	Bulk density	Moisture content	Volatile matter	Ash content	Fixed carbon	HHV	LHV
	[kg.m ⁻³]					[MJ.kg ⁻¹]	[MJ.kg ⁻¹]
BSW 1	520	7,50%	34,30%	24,50%	33,70%	18,2	17,7
BSW 2	550	10,20%	36,00%	25,80%	28,00%	18,4	17,7
BSW 3	560	10,30%	38,80%	19,00%	32,90%	19	18,3

Figure 1: BSW briquettes.

Stoves

Figure 2a illustrates the traditional stove (TCS), currently used in DRC, taken as the reference for our study. It consists of a cylindrical combustion chamber, 100 mm deep and 280 mm in diameter, with holes, 10 to 12 mm in diameter, both in the base and the lateral side [31].

Our improved gasification stove (ICS-G), shown in Figure 2b, generates combustion through two consecutive stages with a stoichiometric proportion of 6 kg of air per 1 kg of biomass to ensure total biomass combustion. The fraction of air that is introduced into the lower part of the reactor (ϵ), respect to the total one used by the stove, is fixed to 0.3 - 0.4, with the purpose to gasify solid biomass into a gaseous element (syngas). The remaining quantity of air, known as secondary air, is introduced at the top of the reactor, and has the function to ensure a complete combustion of the biomass. The number of holes and, therefore, the primary and secondary air inlet sections, are such

that they ensure these air proportions. The different components of this ICS-G are shown at the diagrams in the figure 3.

(a)

(b)

Figure 2: Cooking stoves.

a) Traditional cookstove, TCS. b) Improved Cookstove Gasifier, ICS-G.

Calculation of the improved ICS-G stove dimensions takes into account different aspects [32-36]; in particular, the amount of energy needed to cook a meal for a six-persons household was estimated to be around $Q = 15.8$ MJ [28, 32-33]. Therefore, the minimum power requirement to cook food for a meal for a family of six persons with a burning time in the range 1.0 to 1.5

h [34] is about 3 kW. The rest of this stove design parameters are detailed in table 5.

Table 5: ICS-G design parameters.

Parameter	Symbol	Value
Power	P	3 kW
Stequiometric air	SA	6 kg air/kg biomass
Equivalence ratio	ε	0.33
Air density	ρ_a	1.25 kg.m ⁻³
Thermal efficiency	η_{th}	60%
Cooking time	Δt	1 h
Specific biomass weight	ρ_f	560 kg.m ⁻³
Air holes diameter	d_e	2 mm
Specific gasification rate	SGR	110 kg.m ⁻² .h ⁻¹

The following ICS-G characteristics are deduced

a) Fuel Consumption Rate (FCR): amount of biomass fuel to be used by the stove to provide the required energy, it is deduced by using the relationship (1).

$$FCR = \frac{P*3600}{LCV*\eta_{th}} \quad (1)$$

Where *LCV* represents the fuel low specific calorific power, η_{th} accounts for the gasifier thermal efficiency and P is the power reactor. For this gasifier, the thermal efficiency was initially assumed as 60-70% [28, 33, 35].

b) Reactor Diameter [32, 34-36].

The reactor diameter is a function of the fuel consumption rate and the specific gasification rate (SGR), this one defined as the amount of fuel used per unit of time and per unit of area in the reactor. (110-210 kg.m⁻².h⁻¹) The diameter can be determined using expression (2).

$$D = \left(\frac{4 * FCR}{SGR * \pi} \right)^{0.5} \quad (2)$$

c) Reactor Height: The height of the reactor determines the operation time of the combustion chamber once the fuel is loaded. It is deduced by using equation (3) [32, 34-36].

$$H = \frac{SGR * \Delta t}{\rho_f} \quad (3)$$

Being SGR the specific gasification rate; Δt is the estimated reactor operation time, and ρ_f is the fuel density.

d) Amount of air needed for gasification (Q_{PA}): This magnitude refers to the air flow rate needed to gasify the fuel and it is given by equation (4).

$$Q_{PA} = \frac{\varepsilon * FCR * SA}{\rho_a} \quad (4)$$

Where Q_{PA} is the airflow rate; ε is the gasification equivalence ratio (0.3 to 0.4), FCR is the fuel consumption rate; SA is the stoichiometric amount of air required by unit of biomass (6 kg air per kg biomass) [33], and ρ_a is the air density.

The total amount of air needed for total combustion in the stove is deduced from the above mentioned Q_{PA} , by dividing it by the equivalence ratio ε .

The deduced parameters of a 3 kW stove are deduced using the abovementioned equations and are detailed in table 6.

Table 6: Parameters of a 3 kW reactor.

D [cm]	H [cm]	FCR [kg·h ⁻¹]	Q_{PA} [m ³ ·h ⁻¹]	QAT[m ³ ·h ⁻¹]
12	19	0,906	1.304	4,34

Air is introduced in the combustion chamber (figure 3 a) through the inputs A1 (primary air for gasification) and A2 (secondary air for total combustion). The total air flux A_{ST} is guaranteed by a 3 W fan at 12 V DC. A small speed controller allows for the

regulation of the airflow in the reactor. A lithium-ion battery (12V; 9Ah) and a solar panel (5W) provide the necessary power for the system. The primary air enters through 10 small holes of 2 mm in diameter located 10 mm from the bottom of the reactor. The secondary air enters the reactor through 20 small holes 2 mm in diameter at the top of the stove (figure 3b).

ICS-G stove includes the following components (figure 3c):

- a. Reactor: it is cylindrical, 12cm internal diameter and 19cm deep, and surrounded by a 1cm layer of clay.
- b. Secondary Air Duct Tunnel: Another 16cm cylinder surrounds the reactor, so a 1mm gap allows secondary air to rise, sweeping through the reactor body. This allows preheating of the secondary air.
- c. Thermal insulation: a 4cm layer of rock wool
- d. Fan: A small 3W-12V DC motor provides the primary and secondary air supply.
- e. Power supply: a small 5W solar panel that charges a 9Ah-12V lithium battery.
- f. Regulation: a potentiometric circuit allows varying the supply voltage of the small motor, to control the primary and secondary airflows.
- g. Outer shell: it is a 24cm cube made of 1mm thick sheet metal. The lower base is perforated to allow the motor to inject ambient air

(a)

(b)

(c)

Figure 3: Improved Cookstove Gasifier, ICS-G.
(a: air flows; b: dimensions; c: components)

Instrumentation

The equipment used to characterize the proposed fuel and stove includes:

- Balance OHAUS V11P6 with a 6 kg capacity and 0.1g accuracy. Used to determine the amount of fuel used in the WBT and CCT test.
- Balance OHAUS NVL 20000/2 with a 20 kg capacity and 1 g accuracy. This scale was used to measure the amount of water to boil during the WBT test and the amount of dry and cooked meal during the CCT test.
- Balance Mettler AB304-S / FACT with a 320 g capacity and 0.1 mg accuracy. It was used for the characterization of briquettes
- Select Muffle Furnace SELECT-HORN, Capacity 9 liters. Power 3000 W. Maximum temperature 1100 °C. This

muffle was used for the thermo-physical characterization of briquettes

- Combustion calorimeter CAL2K/1. Resolution 0.001 MJ/kg and 0.000001 °C. To allow for the determination of the calorific value of the briquettes

A Portable Emission Monitoring System (PEMS) was used for the determination of the polluting emissions of CO and PM during the Water Boiling Test, WBT (Fig. 4). This system consists of a bell (a1), inside which the stove to be tested (a2) is placed; an extractor (a3) absorbs all the polluting emissions and takes a sample of the emission gases to take them to the sensor box (a4). Finally, an interface with a data acquisition system, allows for the data storage in a computer (a5).

Figure 4: Portable Emission Monitoring System (PEMS).

Methods

a) Laboratory Tests:

Performance of the ICS-G and the TCS stoves were evaluated by using the WBT 4.2.3 [40] and CCT v.2 [41] laboratory methods. WBT 4.2.3 protocol is a laboratory simulation of the energy

efficiency of the cooking process using water in three sequential phases, as detailed in figure 5. The first phase, High Power Cold Start (HPCS), begins by heating the stove, filled with water from room temperature, up to reach the water boiling point. In the second phase, High Power High Start (HPHS), with the stove already hot from the previous phase, a new refill with fresh water is made and heating starts up to reach again the water boiling temperature. In the third phase, Low Power (LP), the water is maintained for 45 minutes at a temperature close to the boiling point. In the three phases the amount of fuel used for each process is carefully measured. Performance analyzes have been performed in order to compare the traditional stove TCS with the improved ICS-G stove using the new BSW3 fuel. The performance indicators used to compare the stoves are those officially recognized by the IWA, in order to ensure consistency of the selection with the ISO/IWA11:2012 guidelines [42].

Figure 5: Sequential steps in the WBT Protocol [40]

Many studies and researchers suggest that WBT laboratory tests do not necessarily predict the performance of stoves in real domestic kitchens [43-47]. For these reasons, in this investigation the WBT tests were complemented by the CCT tests in which real meals were prepared. In these CCT tests the cooking of a real meal commonly consumed by the population of the area under study is carried out under strict controlled conditions. During the CCT process, three kitcheners prepared

the same meal under identical conditions and with the same amounts of ingredients and water. Total needed time and the amount of fuel used for the food cooking are measured. To allow for the reproducibility of the results and to minimize the margin of error, all the pots used for these tests have the same characteristics and dimensions [48-50], and the cooks prepared six times the same amount of food ($n = 6$). The ingredients used in the tests are shown in Table 7. Each test is based on a total of 12.45 kg of raw material, including cooking water. Final weight after cooking should be 6.58 kg (Standard deviation, $SD=0.10$).

Table 7: Raw material for a CCT test.

	Quantity [g]
Fish (6)	1.370
Flour (corn + cassava)	2.010
Peanut paste	180
Vegetables	1.150
Other ingredients (tomatoes, salt, onion, garlic)	390
Olive oil	350
Water	7.000

This test provides reliable performance indicators of the behavior of the cooking stove when used on the field. These performance indicators are the specific fuel consumption (SFC) and the total cooking time. SFC represents the amount of fuel needed to cook the quantity of food needed for usual meal and it is calculated by:

$$SFC = \frac{W_{fuel}}{W_f} \quad (5)$$

Where W_{fuel} is the mass of fuel used for cooking the meal and W_f is the cooked meal mass.

b) Estimates of CO₂ Emission Reduction (ER-CO₂) for the ICS-G Stove:

The calculations of the ER-CO₂ resulting from the use of non-renewable wood in kitchens are carried out using the AMS-II methodology [51] according to the United Nations Convention on Climate Change (UNFCC). These emissions savings are given by:

$$ER = B_{Savings} * f_{NRB} * NCV_{biomass} * EF \quad (6)$$

Where: $B_{Savings}$ is the amount of woody biomass, in tons, used by the ICS-G during the year; f_{NRB} is the fraction of non-renewable biomass (it can be obtained from some study results or government data, default value for DRC is 90%); $NCV_{biomass}$ is the low specific heat value of the non-renewable woody biomass that is been replaced (in the case of wood, this value is 0.015 TJ/t, using the gross weight of the air dried wood), and EF is the fossil fuel emission factor that is expected to be used for the replacement of non-renewable woody biomass with other commonly available fossil fuels, its value is 63.7 t CO₂/TJ. When charcoal is used as fuel by the reference TCS stove or by the new ICS-G stove, the amount of woody biomass will be determined using a conversion factor of 5 kg of wood (wet) per 1 kg of charcoal (dry base). All these values are obtained from [51].

$B_{Savings}$ can be determined from the results of the CCT tests by using the following relationship:

$$B_{Savings} = B_{Olds} * (1 - \frac{SFC_{New}}{SFC_{Olds}}) \quad (7)$$

Where: SFC_{Olds} and SFC_{New} are the specific fuel consumption for the TCS and the ICS-G stoves, respectively.

Results and Discussion

Performance Analysis Using the WBT Method

Tables 8 shows the results from the WBT tests for both types of stoves when using charcoal as a fuel. Table 9 details the results

when the used fuel is BSW3. All these values have been obtained directly from the PEMS system. In both cases, a significant improvement in energy efficiency of 134% and 153%, respectively, is obtained by using the ICS-G stove, together with a very significant reduction of CO and PM emissions. Comparing the TCS stove using charcoal with the new ICS-G stove using BSW3 briquettes, (Table 10), there was a 150% increase in energy efficiency, saving in fuel of about 67% and CO emission reductions of 41% and 67% during the high and low power test phases, while PM particle emission reduction reaches 84% and 93%, respectively. Therefore, a significant decrease of pollutants and an increase in performance due mainly to the new design of the stove and the new fuel is observed. In a recent study done in a Kenyan village on the impact of a gasifier on improving energy efficiency and reducing polluting emissions, Gitau, J.K. et al. [15] underlines a reduction in CO and PM emissions of 57% and 79%, respectively, when compared with the traditional model. Our improved performance of the ICS-G is mainly due to the improved combustion quality due to the adjustment of the stoichiometric air quantity, which leads to an almost complete combustion of the solid biomass. Forced ventilation (ICS-G) always results in better combustion than natural ventilation (TCS), all other things being equal. In addition, the ICS-G combustion chamber is thermally insulated, this prevents heat loss on the sides of the ICS-G stove and therefore concentrates all the heat produced and directs it towards the pot with the movement of forced air. Natural ventilation does not ensure perfect combustion because its random nature and high dependence on the external atmospheric conditions, as the combustion chamber is not closed, heat losses are uncontrolled and widespread.

Table 8: Results from WBT test using charcoal as fuel.

IWA PERFORMANCE METRICS	UNITS	TCS	ICS-G	ICS-G.vs,TCS (%)
High Power Thermal efficiency	%	$22 \pm 1,0$	51.6 ± 1.5	134 ± 13
Low Power Specific Fuel Consumption	$\text{kJ}/(\text{s}\cdot\text{l})$	0.64 ± 0.05	0.32 ± 0.07	-50.0 ± 11.6
High Power CO emissions	g/MJ	16.3 ± 3.8	5.1 ± 0.2	-68.7 ± 7.4
Low Power CO emissions	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}3$	5.00 ± 0.67	1.33 ± 0.08	-73.3 ± 3.9
High Power PM emissions	$\text{g}/\text{MJ}\cdot 1\text{e-}3$	116 ± 10.7	38.1 ± 2.4	-67.2 ± 9.5
Low Power PM emissions	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}6$	35.0 ± 0.33	20.0 ± 0.4	-42.9 ± 1.1

Table 9: Results from the WBT tests using briquettes BSW3 as fuel.

IWA PERFORMANCE METRICS	UNITS	TCS	ICS-G	ICS-G.vs,TCS (%)
High Power Thermal efficiency	%	21.8 ± 1.2	55.1 ± 0.03	153 ± 14
Low Power Specific Fuel Consumption	$\text{kJ}/(\text{s}\cdot\text{l})$	0.57 ± 0.05	0.19 ± 0.02	-66.7 ± 4.4
High Power CO	g/MJ	16.3 ± 3.8	6.9 ± 0.4	-41.0 ± 3.4
Low Power CO	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}3$	4.83 ± 0.17	1.50 ± 0.17	-66.9 ± 3.7
High Power PM	$\text{g}/\text{MJ}\cdot 1\text{e-}3$	83.3 ± 6.4	13.5 ± 3.1	-83.8 ± 3.9
Low Power PM	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}6$	20.7 ± 2.3	1.5 ± 0.4	-92.8 ± 1.8

Table 10: Comparison TCS/charcoal vs ICS-G/BSW3.

IWA PERFORMANCE METRICS	UNITS	TCS	ICS-G	ICS-G.vs,TCS (%)
High Power Thermal efficiency	%	$22 \pm 1,0$	$55.1 \pm 0,03$	150 ± 11
Low Power Specific Fuel Consumption	$\text{kJ}/(\text{s}\cdot\text{l})$	0.64 ± 0.05	0.19 ± 0.02	-70.3 ± 3.9
High Power CO	g/MJ	11.7 ± 0.07	6.9 ± 0.4	$-41,0 \pm 3,4$
Low Power CO	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}3$	5.00 ± 0.67	1.50 ± 0.17	-70.0 ± 5.3
High Power PM	$\text{g}/\text{MJ}\cdot 1\text{e-}3$	116 ± 10.7	13.5 ± 3.1	-88.4 ± 3.9
Low Power PM	$\text{g}/(\text{s}\cdot\text{l})\cdot 1\text{e-}6$	35.0 ± 0.33	1.5 ± 0.4	-95.7 ± 1.1

Obtained improvement in emissions are in agreement with the results published in [16], where at lower air supply rates, low emissions of both PM and CO are achieved.

Results from the CCT Analysis

Tables 11 and 12 show the results of the CCT tests carried out in the preparation of the typical meal consumed in the city of Bandundu. Table 11 summarizes the comparison between the ICS-G and TCS stoves using charcoal as fuel. A fuel saving of 61% is observed as well as a 20% decrease in the time used for cooking when the improved ICS-G stove is used. This is an improvement on the 40% fuel economy reported in [15] for a natural air gasifier. Table 12 shows the test results using BSW3 as fuel. In this case, ICS-G has very similar fuel savings in relation to the TCS independent of the type of fuel: charcoal or BSW3 than in the previous case, 61%. Similarly, cooking time saving is almost the same for the two kind of fuel: 18% compared to the traditional system. However, BSW3 main advantage comes from the fact that this fuel is obtained from agricultural residues, so no cutting down of trees as in the use of charcoal is needed. Besides, there is a saving in fuel consumption mainly due to the fact that in an ICS-G the firepower can be fully controlled; i.e.: during the simmering phase of the food, the power is reduced with the corresponding fuel saving. For a TCS, it is impossible to vary the fire power during the different phases of the cooking process, given it is based on natural ventilation. Besides, the ICS-G includes a greater thermal insulation, especially in the lateral surface.

Table 11: CCT results (Charcoal as fuel, n=6).

	TCS	ICS-G	ICS-G.vs,TCS (%)
Fuel [g]	2063 ± 119	805 ± 80	-61.0 ± 4.5
Cooking Time [s]	15120 ± 960	12160 ± 612	-20.2 ± 6.5
SFC [g charcoal /kg cooked meal]	313 ± 16.5	123 ± 11.2	-60.7 ± 4.1
SEC[MJ /kg cooked meal]	9.3 ± 0.5	3.7 ± 0.3	-60.2 ± 3.9

Table 12: CCT results (BSW3 briquettes as fuel n=6).

	TCS	ICS-G	ICS-G/TCS[%]
Fuel [g]	3327 ± 210	1270 ± 95	-61.8 ± 3.7
Cooking Time [s]	15960 ± 432	13080 ± 654	-18.0 ± 4.7
SFC [g charcoal /kg cooked meal]	506 ± 27	194 ± 13.0	-61.7 ± 3.3
SEC[MJ /kg cooked meal]	9.3 ± 0.5	3.5 ± 0.2	-62.4 ± 2.9

Table 13: Bsavings and ER-CO₂ for ICS-G.

Fuel	Bsaving (t/year) Household	Bsaving (t/year) Bandundu City	ER- CO ₂ (t/year) Household	ER-CO ₂ (t/year) Bandundu City
Charcoal	2.288	1,248.194	1.97	1,073,384
BWS3	3.766	2,054,480	3.24	1,766,751

Environmental Analysis

By using data from the results in tables 11 and 12, we can deduce that the fuel savings by the introduction of the ICS-G stove instead the TCS is 1.21 kg when using charcoal, and 2.06 kg when using BSW3 briquettes. CO₂ emissions reductions have been calculated according to the AMS-II methodology [51]. Table 13 indicates the annual reduction in wood consumption and CO₂ emissions for a household and for the entire city of Bandundu, where around 90% depend on biomass for cooking food. We are considering that 1 kg of charcoal is equivalent to 5 kg of firewood.

Socioeconomic Analysis

The use of ICS-G with BSW3 fuel will provide significant economic benefits to the households in developing countries. The price of one kilogram of charcoal is estimated at 0.6 \$/kg in Bandundu and the price of BSW3 could be around 0.2 US\$/kg. In accordance with the fuel consumptions deduced in the CTT tests, the daily fuel purchases under current conditions, TCS stove using charcoal, reaches 1.23 US\$/family.day, that would be reduced to 0.48 US\$/family.day when using the ICS-G stove with charcoal and up to 0.25 US\$/family.day if the fuel for this stove would be BSW3. Therefore, monthly savings of US\$ 22.6 will be obtained by the introduction of ICS-G stoves using charcoal and US\$ 29.4 when the fuel used will be BSW3. Taking into account that the purchase price of this ICS-G stove is in the order of 50 US\$, the return periods are 2.2 and 1.7 months, respectively. Therefore, the savings for the first year are US\$ 222 and US\$ 303.5 for the both cases of ICS-G under consideration.

Conclusions

The causes of deforestation and greenhouse gas emissions and pollutants in developing countries, such as those in sub-Saharan Africa, are diverse, but they include in a high percentage the use in cooking activities of traditional fuels with low energy efficiency stoves. A possible solution to reduce deforestation and

the rate of polluting and greenhouse gases emissions would require the improvement of the stoves and the fuels used for those cooking activities. In this work, an improved stove based on gasification and a new fuel obtained from agricultural wastes have been designed and built to address these goals. Results using standard protocols, such as BWT and CCT, indicates fuel savings up to 61% and cooking time reduction of 18% by the introduction of these improvements in stove and fuel. Environmental impact remediation is obtained by wood savings of 2.05 Mt/year, from the substitution of this wood by agricultural wastes, and 1.9 Mt CO₂/year emissions in the case of the Bandundu City in the DRC. Economic improvement is also obtained with these new elements, reaching, for a standard family with 6 members, annual savings up to US\$303 by the introduction of ICS-G stoves with BSW3 fuel and a return period for the investment in the new stove below 2 months

References

1. Abdul Waheed Bhutto, Aqeel Ahmed Bazmi, Sadia Karim, Rashid Abro, Shaukat Ali Mazari, et al. Promoting sustainability of use of biomass as energy resource: Pakistan's perspective. *Environmental Science and Pollution Research*. 2019; 26: 29606-29619.
2. IEA. From Poverty to Prosperity, in *World Energy Outlook Special Report*. Paris: OECD Publishing. 2017. Available Online at: <https://www.oecd.org/publications/energy-access-outlook-2017-9789264285569-en.htm>
3. Maes WH, Verbist B. Increasing the sustainability of household cooking in developing countries: policy implications. *Renewable and Sustainable Energy Reviews*. 2012; 16: 4204–4221.
4. Zhang ZX. Effects of biomass pellet composition on the thermal and emissions performances of a TLUD cooking stove. *Int. J. Agric. & Biol. Eng.* 2017; 10: 189–197.
5. Zhang Y. The Influences of Various Testing Conditions on the Evaluation of Household Biomass Pellet Fuel Combustion. *Energies*. 2018; 11: 1131-1142.
6. Mwampamba TH. Dispelling common misconceptions to improv attitudes and policy outlook on charcoal in

- developing countries. *Energy for Sustainable Development*. 2013; 17: 75–85.
7. Jones D, Ryan CM, Fisher J. Charcoal as a diversification strategy: The flexible role of charcoal production in the livelihoods of smallholders in central Mozambique. *Energy for Sustainable Development*. 2016; 32: 14–21.
8. Chiteculo V. Value Chain of Charcoal Production and Implications for Forest Degradation: Case Study of Bié Province, Angola. *Environments*. 2018; 5: 113-126.
9. Lynch M. Reducing Environmental Damage Caused by the Collection of Cooking Fuel by Refugees. *Canada's Journal on Refugees*. 2002; 21: 18-27.
10. Barbieri, J. Laboratory Testing of the Innovative Low-Cost Mewar Angithi Insert for Improving Energy Efficiency of Cooking Tasks on Three-Stone Fires in Critical Contexts. *Energies*. 2018; 11: 3463-3476.
11. IEA. *World Energy Outlook 2018*. Paris: IEA. 2018. Available Online at: <https://www.iea.org/reports/world-energy-outlook-2018>
12. Ramanathan V, Carmichael G. Global and regional climate changes due to black carbon. *Nature Geoscience*. 2008; 1: 221-227.
13. Ndindeng, Sali Atanga. Evaluation of fan-assisted rice husk fuelled gasifier cookstoves for application in sub-Saharan Africa. *Renewable Energy*. 2019; 139: 924-935.
14. Jagger, Pamela, Das, Ipsita. Implementation and scale-up of a biomass pellet and improved cookstove enterprise in Rwanda. *Energy for Sustainable Development*. 2018; 46: 32-41.
15. Gitau JK. Use of Biochar-Producing Gasifier Cookstove Improves Energy Use Efficiency and Indoor Air Quality in Rural Households. *Energies*. 2019; 12: 4285-4292.
16. Kirch Thomas. Feedstock Dependence of Emissions from a Reverse-Downdraft Gasifier Cookstove. *Energy for Sustainable Development*. 2020; 56: 42-50.
17. Dresen E. Fuelwood Savings and Carbon Emission Reductions by the Use of Improved Cooking Stoves in an Afromontane Forest, Ethiopia. *Land*. 2014; 3: 1137-1157.
18. Barbieri J, Riva F, Colombo E. Cooking in refugee camps and informal settlements: A review of available

- technologies and impacts on the socio-economic and environmental perspective. *Sustain. Energy Technol. Assess.* 2017; 22: 194–207.
19. Tucho GT, Nonhebel S. Bio-Wastes as an Alternative Household Cooking Energy Source in Ethiopia. *Energies.* 2015; 8: 9565-9583.
 20. Smith KR. Greenhouse implications of household stoves: an analysis for India. *Annual. Rev. Energy Environ.* 2000; 25: 741–763
 21. FAO (Food and Agriculture Organization). State of the World's Forest. Rome. 2020. Available online at: <http://www.fao.org/state-of-forests/2020/en/>
 22. La quema de residuos agrícolas: fuente de dioxinas. Comisión para la Cooperación Ambiental, Montreal, Canadá. 2014. Available online at: <http://www3.cec.org/islandora/es/item/11405-la-quema-de-residuos-agricolas-es-una-fuente-de-dioxinas-es.pdf>
 23. Producción y Consumo Sostenible y Residuos Agrarios. M° Agricultura, Alimentación y Medio Ambiente. 2012. Available online at: https://www.miteco.gob.es/images/es/Residuos%20agrarios_tcm30-193059.pdf
 24. Bhojvaid V. How do People in Rural India Perceive Improved Stoves and Clean Fuel. Evidence from Uttar Pradesh and Uttarakhand. *Int. J. Environ. Res. Public Health.* 2014; 11: 1341-1358.
 25. Loo JD. User Perspectives of Characteristics of Improved Cookstoves from a Field Evaluation in Western Kenya. *Int J Environ Res Public Health.* 2016; 13: 167-171.
 26. FAO-ONU. Perspective monde 2020. Available online at: <https://perspective.usherbrooke.ca/bilan/servlet/BMTendanceStatPays?codeTheme=5&codeStat=RS.NUT.PROD.PP.MT&codePays=COD&optionsPeriodes=Aucune&codeTheme2=5&codeStat2=RSA.FAO.RicePaddy&codePays2=COD&optionsDetPeriodes=avecNomP&langue=fr>.
 27. Strategie Nationale De Developpement De La Riziculture (SNDR). 2013. Available online at: https://riceforafrica.net/images/pdf/NRDS_drc_fr-min.pdf

28. Panwar NL, Rathore NS. Design and performance evaluation of a 5 kW producer gas stove. *Biomass & Bioenergy*. 2008; 32: 1349–1352.
29. Panwar NL, Kurchania AK, Rathore NS. Mitigation of greenhouse gases by adoption of improved biomass cookstoves. *Mitig. Adapt. Strateg. Glob. Change*. 2009; 14: 569–578.
30. Normas UNE-AENOR (Spain). Available online at: [https://www.aenor.com/normas-y-libros/buscador-de-normas?k=\(i:7516040\)](https://www.aenor.com/normas-y-libros/buscador-de-normas?k=(i:7516040))
31. Hurtado EJ. Analyse des impacts économique-environnementaux du changement d'usage d'un foyer de cuisson traditionnel par un foyer de cuisson amélioré optimisé à charbon de bois dans les ménages de la ville de Kinshasa. *Déchets sciences et techniques*. 2017; 75: 1-9.
32. Kumar S, Pitchandi K, Natarajan E. Modeling and simulation of down draft wood gasifier. *J. Applied Sci*. 2008; 8: 271-279.
33. Belonio AT. Rice husk Gas stove Handbook. Appropriate Technology Center. Central Philippine University. 2005. Available online at: https://www.bioenergylists.org/stovesdoc/Belonio/Belonio_gasifier.pdf.
34. Ojolo SJ, Abolarin SM, Adegbenro O. Development of a Laboratory Scale Updraft Gasifier. *International Journal of Manufacturing Systems*. 2012; 2: 21-42.
35. Panwar NL. Design and performance evaluation of energy efficient biomass gasifier based cookstove on multi fuels. *Mitig. Adapt. Strateg. Glob. Change*. 2009; 14: 627–633.
36. Mukunda HS. Understanding combustion. Universities Press (India) Private Limited Publication, Hyderabad. 1989.
37. Panwar NL. Design and performance evaluation of energy efficient biomass gasifier based cookstove on multi fuels. *Mitig. Adapt. Strateg. Glob. Change*. 2009; 14: 627–633.
38. Mukunda HS. Understanding combustion. Universities Press (India) Private Limited Publication. Hyderabad. 1989.
39. Kumar H, Panwar NL. Experimental investigation on energy- efficient twin- mode biomass improved cookstove. *SN Applied Sciences*. 2019; 1: 760-768.

40. Water Boiling Test, version 4.2.3. Washington: Global Alliance for Clean Cookstoves. 2014. Available online at: <https://www.cleancookingalliance.org/binary-data/DOCUMENT/file/000/000/399-1.pdf>
41. Bailis R. Performance Testing Protocols Controlled Cooking Test (CCT) Version 2.0. Shell Foundation. University of California Berkeley. 2004. Available online at: <https://www.cleancookingalliance.org/binary-data/DOCUMENT/file/000/000/80-1.pdf>
42. ISO/TMBG Technical Management Board. Guidelines for Evaluating Cookstove Performance. 2012. Available online at: <https://www.iso.org/standard/61975.html>.
43. Jetter JJ, Kariher P. Solid-Fuel household cook stoves: Characterization of performance and emissions. *Biomass & Bioenergy*. 2009; 33: 294–305.
44. Berrueta V, Edwards R, Masera O. Energy performance of wood-burning cookstoves in Michoacan, Mexico. *Renewable Energy*. 2008; 33: 859–70.
45. Smith KR. Monitoring and evaluation of improved biomass cookstove programs for indoor air quality and stove performance: conclusions from the Household Energy and Health Project. *Energy for Sustainable Development*. 2007; 12: 5-18.
46. Bailis R. Performance testing for monitoring improved biomass stove interventions: experiences of the Household Energy and Health Project. *Energy for Sustainable Development*. 2007; 11: 57-70.
47. Baldwin SF Biomass Stoves: Engineering Design, Development, and Dissemination, 287, Center for Energy and Environmental Studies. Princeton University. 1986. Available online at: <http://blog.newdawnengineering.com/website/library/Papers+Articles/Biomass%20Stoves,%20Engineering%20Design,%20Development%20and%20Dissemination,%20Samuel%20Baldwin%201987.pdf>
48. McCarty N. A laboratory comparison of the global warming impact of five major types of biomass cooking stoves, *Energy sustain. Dev*. 2008; 12: 56-65.
49. Lombardi F. Laboratory protocols for testing of Improved Cooking Stoves (ICSs): A review of state-of-the-art and

- further developments. *Biomass & Bioenergy*. 2017; 98: 321–335.
50. Lombardi F, Riva F, Colombo E. Dealing with small sets of laboratory test replicates for Improved Cooking Stoves (ICSs): Insights for a robust statistical analysis of results. *Biomass & Bioenergy*. 2018; 115: 27–34.
51. Small-Scale Methodology: Energy Efficiency Measures in Thermal Applications of Non-Renewable Biomass. UNFCCC 2019. Available online at:
<https://cdm.unfccc.int/methodologies/DB/ZI2M2X5P7ZLRGFO37YBVDYOW62UHQP>